

INSTANT UPRIGHT

Span 300 Instruction Manual



DESIGNATION
SPAN300 Double Width
EN 1004 – 3 – 8/12 – XXCD
SPAN 300 Single Width
EN 1004 – 3 – 8/8 – XXCD

CEN designation of this instruction manual
EN 1298 – IM – en
Rev-00



SAFE WORKING LOADS AND WORKING HEIGHTS


The safe working load at each level of platform is 360kg evenly distributed, regardless of whether one or two platforms are installed. Therefore, even if two platforms are installed side by side, total cumulative load shall not exceed 360kg distributed.

The total loading on the tower structure should not exceed 720kg. Normal maximum platform height for indoor use is 12m for Double Width, and 8m for Single Width. For outdoor use, the maximum height is 8m for Single and Double Widths.

ASSEMBLY PROCESS

1. Preparation

- Locate the tower level adjusters on each leg at 10cm (4 inches) from the bottom of the leg.
- Unlock the interlock clips on all frames.
- When installed, always move the interlock clip to the “locked” position.
- Sort the braces into horizontal and diagonal braces - the diagonals are slightly longer.
- Unlock the brace locks.




2. Base

Step 1: Install castor into adjustable leg.

Step 2: Ensure interlock clips are released from the base frames (bottom frames)..


Step 3: Install castor / leg assembly to frame by pushing the leg into the frame tube. This should be done with manual force only, no tools.

Step 4: Lock castors before ascending any part of the tower.



3. Locking down the platform (Windlock)

A windlock clip is installed on the platform at the hook. This is locked as shown here.



USAGE ADVICE

- We recommend a minimum of two people to assemble, dismantle and move the platform tower.
- Check that all components are on site and in good working order.
- Ensure that the assembly location is checked to prevent hazards during assembly, dismantling or moving and while working on the tower. Particular attention should be given to the ground condition, whether level or sloping, obstructions and wind conditions. The ground condition must be capable of supporting the tower structure.
- Towers must always be climbed from the inside of the assembly using the ladder.
- Adjustable legs must only be used to level the tower and leg extension must be minimised before the tower is moved (max 150mm).
- Lifting of components must be done inside the effective base area of the tower; components are normally hoisted using a rope.
- Moving the tower must only be done by manual effect from the base of the tower.
- When moving tower be aware of overhead hazards (e.g. electric cables).
- No personnel or material to be on the platform whilst the tower is being moved.
- Beware of horizontal loads which can lead to instability of the tower. The maximum side force is 20kg.
- When tying-in the tower, attach a tie to each upright at 4m height intervals. Ensure that couplers are suitable for 50mm diameter aluminum tube.
- Do not use boxes or steps to gain additional height. If extra height required, contact your distributor to get extra components.
- Do not lift or suspend an assembled mobile tower.
- Damaged components or components from other tower systems must never be used.
- Stabilisers should always be fitted when specified. Use the stabiliser shown on the component list according to the tower height.
- When wind exceeds Beaufort force 4, cease using the tower.
- If wind is expected to reach Beaufort force 6, tie tower to a rigid structure.
- If winds of Force 8 are forecast, dismantle the tower or remove to shelter.

Wind speeds				
Force	Peak mph	Peak km/h	Peak m/s	Guidance
4	18	29	8.1	Moderate breeze - raises dust & loose paper
6	31	50	13.9	Strong breeze - difficult to use umbrella
8	48	74	20.8	Gale force - walking is difficult

CARE AND MAINTENANCE

- Keep all equipment clean, especially spigots and sockets where frames join. Spigots should fit easily into sockets. Lubricate with light oil.
- Remove dirt or paint from adjustable legs with a light brush, lightly oil the leg locks.
- Do not strike or hammer components. Do not throw or drop onto hard surfaces.
- Lightly oil spring mechanism of the hooks.
- For transport and storage, components are best stored vertically.
- Damaged parts should be repaired or replaced. Contact your equipment supplier for advice.

DISMANTLING / MOVING TOWERS

To dismantle, follow the build process but in reverse order noting the following.

- To remove the guardrail frames or braces, first unlock the hook at the end away from the trapdoor.
- Sitting through the trapdoor, unlock the near end hook and remove the brace.

To Move the tower to a new position, first prepare the tower.

- Wind speed should not exceed 29 km/h (8.1 m/s).
- Check for overhead obstructions including electrical wires.
- Ensure tower is empty (material and personnel).
- Ensure leg extension is minimised (Max 150mm)Release the castor brakes.
- Raise the stabiliser feet only enough to clear obstructions.
- Move the tower manually by applying force at the base - do not use machinery to push or pull the tower. Once moved - prepare the tower for use.
- Check all castors and stabilisers are in firm contact with the ground.
- Check tower is vertical (spirit level) and adjust legs as required.
- Reapply the castor brakes.

3-T SAFETY STANDARD - THROUGH THE TRAP

This is an approved method of tower construction which, if carried out by a competent person, complies with current safety legislation.

Construction- basic principles

- Always install the trapdoor over the ladder (if one is fitted).
- Ensure the trapdoor hinges to the outside of a double width tower (not to the centre).
- Once the platform has been installed, climb, using the approved method and sit in the trapdoor opening.
- While seated, attach horizontal braces to the frames to form guardrails on both sides of the platform.
- See assembly instructions for specific placement of guardrails.
- 2 braces are normally required each side; although bracing frames can be used on the outside if desired or specified in the instructions.
- Only when the platform is fully guarded is it safe to stand up on the platform.

Dismantling

- Unlock the brace ends furthest away from the trapdoor.
- Sit through the trapdoor as per Fig.1
- Do not remove braces until sitting in the trapdoor.
- NEVER STAND ON AN UNGUARDED PLATFORM.



Fig 1

STABILISERS

Outriggers are to be used, when specified, to guarantee the structural stability of the tower. In addition, the ballast table is to be observed.





Fig 2



Fig 3




Fig 4

ALWAYS ENSURE STABILISER SIZE IS CORRECT AND ABLE TO SUPPORT TOWER

Lightly tighten the upper clamps above the sixth rung on each corner post. Position the lower clamp above the bottom rung. Ensure the lower arm is as horizontal as possible. Position the stabilisers so that the footpads are approximately equidistant from each other, as shown in Fig.2. Adjust the outrigger and reposition the clamps as required to make firm contact with the ground. Ensure the clips with locking pin are in place. When in the correct position, tighten the clamps firmly.

To position the tower against a wall, do not remove the stabiliser; move parallel with the wall. (Fig.3)

To position the tower in a corner, remove the inside stabiliser and place the outside two parallel with the wall. (Fig.4)


Ballast weight maybe used to stabilise the tower, please contact your supplier for the correct amount of ballast weight required.

SPECIFIC PRODUCT INFORMATION

Table of parts and quantities

Span 300 Double Width Towers - 2m, 2.5m and 3m lengths to EN1004									
Platform Height (m)	2m	4m	6m	8m	10m	12m			
Work Height (m)	5	6	8	10	12	14			
Tower Height (m)	4	5	7	9	11	13			
Tower Weight in kg (2m length)	138	185	235	292	342	393			
Tower Weight in kg (2.5m length)	153	206	263	327	384	441			
Tower Weight in kg (3m length)	166	223	285	354	416	478			
Note: Quoted platform heights included 150mm (6 inches) leg adjustment for leveling that can be increased or reduced									
Description	Weight (kg)								
7 Rung Frame	11.2			2	4	6	8	10	12
4 Rung Frame	8.5			2	2	2	2	2	2
Trapdoor Platform	14	18	20	1	2	3	4	5	6
Fixed Platform	14	17	20	1	1	1	1	1	1
Horizontal Brace	1.7	2	2.4	1	5	9	13	17	21
Diagonal Brace	1.8	2.2	2.5	4	8	12	16	20	24
Telescopic Stabiliser (50430)	5.2			4	4	4			
Large Stabiliser (9090)	6.8						4	4	4
Adjustable Leg	1.1			4	4	4	4	4	4
Castor / Baseplate	2.2			4	4	4	4	4	4
Toe-board set	8.7	11.5	14.4	1	1	1	1	1	1
Guardrail bracing frame	3.8	4.4	5.2	2	2	2	2	2	2






Exploded diagram & reference list






Tower Assembly

1. Castor
2. Adjustable Leg
3. 4 Rung Frame
4. Platform
5. Horizontal Brace
6. 7 Rung Frame
7. Diagonal Brace
8. Toeboard
9. Bracing Frame
10. Interlock Clip
11. Outrigger



DOUBLE-WIDTH TOWER 6m



DOUBLE-WIDTH TOWER 6m



DOUBLE-WIDTH TOWER 6m



DOUBLE-WIDTH TOWER 6m

19




SPECIFIC PRODUCT INFORMATION

Table of parts and quantities

Span 300 Single Width Towers - 2m, 2.5m and 3m lengths to EN1004							
Platform Height (m)			2m	4m	6m	8m	
Work Height (m)			4	6	8	10	
Tower Height (m)			3	5	7	9	
Tower Weight in kg (2m length)			103	144	186	234	
Tower Weight in kg (2.5m length)			112	159	207	261	
Tower Weight in kg (3m length)			120	171	223	281	
Note: Quoted platform heights included 150mm (6 inches) leg adjustment for leveling that can be increased or reduced							
Description	Weight (kg)						
7 Rung Frame	11.2			2	4	6	8
4 Rung Frame	8.5			2	2	2	2
Trapdoor Platform	14	18	20	1	2	3	4
Horizontal Brace	1.7	2.0	2.4	1	5	9	13
Diagonal Brace	1.8	2.2	2.5	2	4	6	8
Bracing frame	3.8	4.4	5.2	2	2	2	2
Telescopic Stabiliser (50430)	5.2			4	4	4	
Large Stabiliser (9090)	6.8						4
Adjustable Legs	1.1			4	4	4	4
Castor / Baseplate	2.2			4	4	4	4
Toe-board set	1.8	2.2	2.5	1	1	1	1






Exploded diagram & reference list






Tower Assembly

1. Castor
2. Adjustable Leg
3. Horizontal Brace
4. Diagonal Brace
5. 4 Rung Frame
6. Platform
7. 7 Rung Frame
8. Toeboard
9. Bracing Frame
10. Interlock Clip
11. Outrigger

SINGLE-WIDTH TOWER 6m



SINGLE-WIDTH TOWER 6m



SINGLE-WIDTH TOWER 6m

